



型號	重量 grf	JIS2級 S	D	L	L ₁	L ₂	L ₃	D ₁	W 0 -0.3	D ₂
RBI 5	25	M 5x0.8	9	46	24	4	12	11	9	17
RBI 6	40	M 6x1	10	55.2	28	5	15	13	11	20
RBI 8	75	M8x1.25	12.5	65	32	5	16	16	14	24
RBI 10	120	M10x1.25	15	74.5	35	6.5	18	19	17	28
RBI 10B	123	M10x1.5		80.5						
RBI 12	185	M12x1.25	17.5	84	40	6.5	20	22	19	32
RBI 12B	190	M12x1.75		91						
RBI 14	275	M14x1.5	20	103	45	8	25	25	22	36
RBI 14B	280	M14x2		109						
RBI 16	360	M16x1.5	22	112	50	8	27	27	22	40
RBI 16B	370	M16x2		118						
RBI 18	535	M18x1.5	25	130.5	58	10	32	31	27	45
RBI 20	570	M2x1.5	27.5	133	63	10	38	34	30	45
RBI 22	755	M22x1.5	30	145	70	12	43	37	32	50

軸徑 d H9	ℓ ₁	ℓ ₂ ±0.3	ℓ ₃	d ₁	w 0 -0.3	d ₂	容許 傾斜角 θ	降伏點強度 pk kgf	靜負荷 Cs kgf	容重 Cs kgf
5	22	11	8	9	7	20	30°	290	580	1160
6	27.2	12.2	11	10	8	20	30°	380	760	1520
8	33	16	12	12	10	24	30°	600	1190	2370
10	39.5	19.5	15	14	11	30	30°	860	1710	3420
	45.5		21							
12	44	21	17	19	17	32	30°	1160	2330	4650
	51		24							
14	58	23.5	22	19	17	38	22°	1520	3040	6080
	64		28							
16	62	25.5	23	22	19	44	22°	1520	3040	6080
	68		29							
18	72.5	31	25	23	20	45	22°	1930	3850	7690
20	70	29	25	29	24	50	15°	1930	3850	7690
22	75	33	26	27	24	52	15°	2400	4750	9500