


3 PIECE, HIGH STRENGTH ALLOY, HEAVY DUTY SHANK
METAL-TO-METAL

RMX



| PART NO. | | DIMENSIONS IN INCHES | | | | | | | | | | Radial Static Load Cap. Lbs. | Approx. Brg. Wt. Lbs. |
|------------|-----------|---------------------------|------------------------|---------------|----------------|---------------|----------------|-------|---------------|------------------|--------|------------------------------|-----------------------|
| Right Hand | Left Hand | B | W | H | A | D | Ball Dia. Ref. | C | Thread UNF-3A | a' Max/Min Angle | | | |
| RMX3 | RMXL3 | .1900 +.0015 -.0005 | .312 +.000 -.005 | .250 ±.005 | 1.562 ±.015 | .750 ±.010 | .437 | 1.000 | 1/4-28 | 10 | 5.260 | .043 | |
| RMX4 | RMXL4 | .2500 | .375 | .281 | 1.875 | .875 | .500 | 1.250 | 5/16-24 | 13 | 8.452 | .072 | |
| RMX5 | RMXL5 | .3125 | .437 | .344 | 1.938 | 1.000 | .625 | 1.250 | 3/8-24 | 12 | 12.978 | .112 | |
| RMX6 | RMXL6 | .3750 | .500 | .406 | 2.125 | 1.125 | .719 | 1.375 | 7/16-20 | 10 | 17.508 | .160 | |
| RMX7 | RMXL7 | .4375 | .562 | .437 | 2.438 | 1.312 | .812 | 1.500 | 1/2-20 | 12 | 23.452 | .249 | |
| RMX8 | RMXL8 | .5000 | .625 | .500 | 2.625 | 1.500 | .937 | 1.625 | 5/8-18 | 10 | 31.390 | .362 | |
| RMX10 | RMXL10 | .6250 | .750 | .562 | 2.875 | 1.750 | 1.125 | 1.750 | 3/4-16 | 13 | 40.572 | .602 | |

| PART NO. | | DIMENSIONS IN MILLIMETERS | | | | | | | | | | Radial Static Load Cap. Kilograms | Approx. Brg. Wt. Grams |
|------------|-----------|---------------------------|------------------------|---------------|----------------|----------------|----------------|-------|---------------|------------------|--------|-----------------------------------|------------------------|
| Right Hand | Left Hand | B | W | H | A | D | Ball Dia. Ref. | C | Thread UNF-3A | a' Max/Min Angle | | | |
| RMX3 | RMXL3 | 4.83 +.0381 -.0127 | 7.92 +.000 -.127 | 6.35 ±.127 | 39.67 ±.381 | 19.05 ±.254 | 11.10 | 25.40 | 1/4-28 | 10 | 2.386 | 20 | |
| RMX4 | RMXL4 | 6.35 | 9.53 | 7.14 | 47.63 | 22.23 | 12.70 | 31.75 | 5/16-24 | 13 | 3.834 | 33 | |
| RMX5 | RMXL5 | 7.94 | 11.10 | 8.74 | 49.23 | 25.40 | 15.88 | 31.75 | 3/8-24 | 12 | 5.887 | 51 | |
| RMX6 | RMXL6 | 9.53 | 12.70 | 10.31 | 53.98 | 28.58 | 18.26 | 34.93 | 7/16-20 | 10 | 7.942 | 73 | |
| RMX7 | RMXL7 | 11.11 | 14.27 | 11.10 | 61.93 | 33.32 | 20.62 | 38.10 | 1/2-20 | 12 | 10.638 | 113 | |
| RMX8 | RMXL8 | 12.70 | 15.88 | 12.70 | 66.68 | 38.10 | 23.80 | 41.28 | 5/8-18 | 10 | 14.239 | 173 | |
| RMX10 | RMXL10 | 15.88 | 19.05 | 14.27 | 73.03 | 44.45 | 28.58 | 44.45 | 3/4-16 | 13 | 18.403 | 273 | |

MATERIALS

| BALL | RACE | BODY |
|--|---|---|
| S2100 STEEL R/C 56 MIN. HARD CHROME PLATED | STEEL ALLOY HEAT TREATED ZINC PLATED, CHROMATE TREATED | STEEL ALLOY HEAT TREATED ZINC PLATED, CHROMATE TREATED |